

ICE34 Iceberg Standpipe

with 22m Snap Coupling (Mark III)

The galvanised ICE34 Iceberg unit is designed to expose 150mm above ground, offering a non-intrusive hidden profile with lockable cover.

The unit is manufactured in heavy-duty galvanised mild steel, ensuring longevity and durability.

A quick release snap couplings (GEKA) are fitted as standard to this unit, making it ideal for irrigation purposes. A double check valve is fitted in the above ground section allowing this model to be connected to a mains water supply. All internal plumbing is insulated to protect against severe weather fluctuations

N.B. The water user must decide upon the backflow requirements necessary for each installation.

ICE34 Standpipe Specification:

ICE34 Shell	
Material	Pre-Galvanised Mild Steel (2mm Thickness)
Unit Length	930mm (150mm above ground profile - 780mm installed below ground level).
Unit Section	220mm x 145mm
Outlet Tap Cover	225mm x 160mm x 28mm
Stabilising Base Plate	375mm x 195mm
ICE34 Plumbing	
Double Check Value	22mm DCV (WRAS Approved)
Outlet Tap	3/4" Brass Snap Coupling (GEKA)
Stop Tap	22mm Lever Tap
Mains Connection	Melomatic MDPE Coupler
Internal Rising Main	25mm MDPE
Insulation	Polyflex expanded foam or equivalent insulator, giving protection down to -5 degrees Celsius

