

NON12 Tower Standpipe

with 1/2" Non Concussive Bib Tap (Mark III)

Manufactured in high quality stainless steel, the NON12 is the definite choice for a safe and secure water supply.

The high quality stainless steel shell offers; longevity, durability, lockable covers for vandal resistance and pleasing aesthetics. The Edwards NON12 standpipe is ideal for all areas of public access.

Although this unit has been designed to accommodate fluctuations in severe weather conditions, it is important that in extreme cold weather the unit should be drained to avoid frost damage.

Also Available with TYPE ESRS Self Regulating Heating Tape (Wattage: 10Watts @ 10DegC ; Voltage: 240V). www.eshltd.com. Please call 01584 861223 or email for further information.

N.B. The water user must decide upon the backflow requirements necessary for each installation.

NON12 Standpipe Specification:

NON12 Shell

Material	Brushed Stainless Steel (Grade 304 - 1.5mm Thickness)
Unit Length	1470mm (720mm above ground profile - 750mm installed below ground)
Unit Section	106mm x 106mm
Outlet Tap Cover	225mm x 180mm x 120mm
Stop Tap Cover	70mm x 260mm x 110mm
Stabilising Base Plate	255mm x 205mm

NON12 Plumbing

Double Check Value	15mm DCV (WRAS Approved)
Outlet Tap	1/2" CAPRI Non Concussive Bib Tap (Chrome Finish)
Stop Tap	15mm Brass Stop Tap (EN 1213)
Drain Off Tap	Type A. Brass Drain Valve
Mains Connection	20mm MDPE
Internal Rising Main	15mm Polypipe
Insulation	Polyflex expanded foam or equivalent insulator, giving protection down to -5 degrees Celsius

